

# MSDS for Omin-Vials

## Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard. 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor  
Occupational Safety and Health Administration  
(Non-Mandatory Form)

IDENTITY (As Used on Label and List) E-217 Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

### Section I

Manufacturer's Name <u>Tri-Seal International, Inc.</u>	Emergency Telephone Number <u>845 353-3302</u>
Address (Number, Street, City, State, and ZIP Code) <u>900 Bradley Hill Road</u>	Telephone Number for Information <u>845 353-3300</u>
<u>Blauvelt, N.Y. 10913</u>	Date Prepared <u>12/7/91</u>
Signature of Preparer (optional)	

### Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
---	----------	-----------	--------------------------	-------------

"According to our interpretation of the Hazardous Products Act and regulations promulgated thereunder, this product should not be considered toxic if used as intended."

A Polyethylene Coextrusion

### TRANSPORTATION INFORMATION

- DOT (USA) Classification: Not regulated
- TDG (Canada) Classification: Not regulated

### Section III — Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H <sub>2</sub> O = 1)	0.417
Vapor Pressure (mm Hg.)	N/A	Melting Point	110° C
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A

Solubility in Water Insoluble

Appearance and Odor White or colored to order - Oderless

### Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) <u>N/A</u>	Flammable Limits	LEL <u>N/A</u>	UEL <u>N/A</u>
--------------------------------------	------------------	----------------	----------------

Extinguishing Media Water spray-Fogging nozzle, dry chemical foam or Carbon Dioxide

Special Fire Fighting Procedures Firefighters should wear self-contained breathing apparatus in the positive pressure mode when there is a possibility of exposure to smoke, flames or decomposition of products.

Unusual Fire and Explosion Hazards

(Reproduce locally)

OSHA 174, Sept. 1985

Sheet# Omni-Vials  
REV.040606

# MSDS for Omin-Vials

## Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid Temperature above 600 F in presence of oxygen
	Stable	X	

Incompatibility (Materials to Avoid) Nitric Acid, Perchloric acid & free Halogens

Hazardous Decomposition or Byproducts Carbon Monoxide, Aldehydes, Acetic Acid

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

## Section VI — Health Hazard Data

Route(s) of Entry: Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic)

Carcinogenicity: N/A NTP? None IARC Monographs? None OSHA Regulated? None

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures None

## Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Normal procedures for clean up. Use good housekeeping practices.

Waste Disposal Method Use normal garbage disposal methods according to local, State & Federal regulations.

Precautions to Be Taken in Handling and Storing No special precaution required. Store in cool area.

Other Precautions

## Section VIII — Control Measures

Respiratory Protection (Specify Type) N/A

Ventilation	Local Exhaust	Special
	Mechanical (General)	Other

Protective Gloves N/A Eye Protection

Other Protective Clothing or Equipment N/A

Work/Hygienic Practices Clean hands after contact as with normal hygienic practice.